



AquaFlor Premier™ Laminate

Product Specifications

1. DETAILS

HDF-Board: CARB 93120 Phase 2 and TSCA Title VI compliant

Thickness: 0.39" (10 mm) + 2mm acoustic backer = 12mm

Width: 8.03" (204 mm)

Length: 47.64" (1210 mm)

Edges: Beveled Edge

Wear Resistance: AC4

Indentation: IC3

Planks per Carton: 6

Square Feet per Carton: 15.94 (1.48 m²)

Weight per Carton (Lbs.): 30.16 lbs. (13.68 kg)

Cartons per Pallet: 24

Country of Origin: USA

GreenGuard Gold Certified

Carb II Compliant: Yes

Resists moisture due to mopping and everyday household spills for a period of up to 24 hours.

2. INSTALLATION - See package insert for complete Installation Information.

Use: Residential / Light Commercial

Installation System: T-Lock, Angle-Tap

Location: Below, on and above grade concrete, approved underlayment grade plywood and approved existing floors.

- Tarkett laminate flooring shall acclimate to the temperature of the room. Place unopened cartons of laminate lying horizontally in the room in which they will be installed for a minimum of 48 hours before installation.
- Room temperature shall be a minimum of 65°F (18°C). Relative humidity shall be between 40% and 70%.
- Substrate shall be level to within 1/8" in 8 feet (3.18 mm in 2.4 m).
- Install a 10mil polyethylene vapor retarder when installing over concrete.
- A minimum 5/16" space is required between flooring and all verticals (walls, cabinets, pipes, etc.).
- Rooms over 30' (9.14 m) in length or width will require the use of Tarkett T-Molding.
- Planks are installed by inserting the long side tongue into the groove side of the previous row at approximately a 30° angle. Position the plank so it is aligned with the short side of the previous plank. Rotate the plank downward to engage the long and short side joints.
- The first and last plank in each row shall be at least 12" (30.4 cm) in length. Stagger end joints a minimum of 12" (30.4 cm).
- Fill expansion perimeter, t-molding spaces and other open areas with 3/8" compressible PE foam backer rod. Cover the backer rod and any remaining gaps with 100% silicone sealant. Do not use acrylic sealants.

3. WARRANTY - See package insert for complete Warranty Information.

- LIFETIME LIMITED RESIDENTIAL WARRANTY
- 10 YEAR LIMITED LIGHT COMMERCIAL WARRANTY

4. CARE AND MAINTENANCE

- Post installation temperature must be maintained between 65°F and 85°F. Relative humidity must be maintained between 40% and 70%.
- Never slide heavy furniture or appliances across the floor. Place plywood on the floor and move the object across the plywood.
- To minimize scratching, equip tables and chairs with proper floor protectors.
- To help prolong the life of the floor, use walk-off mats at outside entrances to collect dirt and debris and excess moisture.
- Sweep or vacuum to remove loose dirt or debris that can scratch the floor.
- Do not leave any topical moisture on the floor for more than 24 hours (water, juice, soft drinks, spill, etc). Spills should be cleaned immediately with a dry cloth.
- When necessary, sweep or dust mop. Wet mop occasionally using a well wrung out mop and water only. Do not pour liquid directly on floor or use an excessively wet mop that will leave puddles or moisture standing on the floor. Never use a steam cleaner, jet mop, buffer, or similar product.



Tarkett North America

Technical Services Department

30000 Aurora Road

Solon, Ohio 44139

888-639-8275 Fax 440-498-0025

northamerican.technicalsupport@tarkett.com

www.tarkettna.com